

4

3

2


1

SHOWN AT MID-STROKE

REVISIONS					
ZONE	LETTER	DESCRIPTION	DATE	CHECKED	APPROVED

D

D



C

C

M3X0.5
0.12 (3) DP


M3X0.5
0.12 (3) DP

B

B

INTERMITTENT FORCE @10% DUTY CYCLE	2.23 N	8.0 OZ
CONTINUOUS FORCE	0.71 N	2.5 OZ
FORCE CONSTANT	0.84 N/A	3.0 OZ/A
BACK EMF CONSTANT	0.84 v/m/s	0.021 v/in/s
STROKE	38.1 mm	1.50 IN
COIL CLEARANCE PER SIDE	0.33 mm	0.013 IN
COIL ASSY MASS	14.6 GR	0.52 OZ
BODY MASS	25.0 GR	0.88 OZ
COIL RESISTANCE	8.5 Ohms	
COIL INDUCTANCE @120 Hz	1.4 mH	
MAX CONTINUOUS POWER	6.0 W	

ALL VALUES AT 25°C



THIS DOCUMENT, WHETHER OR NOT MARKED AS PROPRIETARY, IS CONSIDERED CONFIDENTIAL AND SHALL REMAIN THE PROPERTY OF MOTICONT AND SHALL BE RETURNED TO MOTICONT UPON REQUEST WITH ALL COPIES MADE THEREOF. THIS DOCUMENT CANNOT BE UTILIZED IN THE MANUFACTURE OF ARTICLES SOLD OR OFFERED OR DISCLOSED TO ANYONE AND NO USE OF IT CAN BE MADE UNLESS EXPRESSLY AUTHORIZED BY AND UNDER THE DIRECTION OF MOTICONT. POSSESSION OF THIS DOCUMENT IS ACCEPTED SUBJECT TO THE FOREGOING.

A

A

NOTES :
UNLESS OTHERWISE SPECIFIED

DIMENSIONS ARE IN INCHES (mm) TOLERANCES ON: DECIMALS FRACTIONS ANGLES .XXX .XX ± 1/125 ± 1/2' ± .005 ± .01 UNLESS OTHERWISE SPECIFIED		MATERIAL	CONTRACT		MOTICONT LINEAR VOICE COIL MOTOR			
FINISH TBD		DRN						
USED ON		NEXT ASSY		CHKD			LVCM-013-044-02M	1
APPLICATION		APPVD			SCALE: 2 / 1		SHEET 1 OF 1	

4

3

2

1